

KIN Architectural





Kin Architectural IC62ST

It's a problem solver, addresses unique situations, and is a great sounding solution. The IC62ST is a single piece stereo speaker, equipped with two sets of speaker inputs and two ceramic coated aluminum dome tweeters so it is prepared for distinct left and right input signals. Ideal for smaller areas where pairs might be inconvenient, or as a clever space saving method for surround channels. It has all the features of Kin Architectural and the sonic signature of Totem in one convenient speaker.

MHEX Woofer



Composed of multiple layers of phenolic honeycomb and woven synthetics, MHEX woofers are extremely strong and light. They can handle a lot power and

produce powerful yet controlled bass.

Cast Frames



Tremendously strong, resistant to distortion causing resonances and the manufacturing

process permits larger, stronger driver components to be used.

1" Ceramic coated aluminum dome tweeter



An aluminum dome receives a ceramic coating that improves the stiffness and damping characteristics for the most natural, distortion-free sound.



Low Volume Intelligibility Switch

Fine tunes the output at low listening levels to improve the clarity

of vocals and maintain bass response normally lost at low volume.



Unified Framework Shield is a ribbed, connected cover that protects the speaker from material within walls and ceilings during the

installation process and reinforces the rigidity of the framework to eliminate resonance.



Pivoting tweeter faceplate aims the directional high frequencies towards the listening area.





KIN Architectural



Specifications

Model: IC62ST

Design: 6.5" In-Ceiling 245.1mm/9.65"

Frequency Response: 49 Hz - 30 kHz ± 3 dB

Recommended Power: 20-100 W

Woofer: 6.5" MHEX Phenolic Honeycomb Woven Hybrid woofer Tweeter: Dual 1" Ceramic coated aluminum dome tweeters

Impedance: 8 ohm Sensitivity dB @1W-1M 90dB

Dimensions (r x d): 245.1 x 119.7mm / 9.65 x 4.7"

With Back Can: 157mm / 6.19" 119.7mm/4.7"

Cutout 213mm / 8.38"

Grille type: Magnetic, paintable, virtually bezel-less white metal **Accessories/Options** Pre-construction brackets, square grilles, back can

Speaker Terminals: Spring loaded Gold Plated Speaker Wire: Accepts up to 12 gauge


Dispersion pattern: 75 degrees





157mm/6.19"

Accessories



The PCK6C color coded preconstruction kit is equipped with joist brackets that allows speakers to be installed in a perfect line simply and flawlessly, and multiple points to connect the wings guarantees that contact with drywall is always within access.



The ABC6ST Acoustic Back Can reduces sound from penetrating adjacent rooms by 24dB. It also protects the components from materials, dirt, and dust that can cause damage and degrade performance. Acoustic Back Cans greatly improves the weather resistance of all kin Architectural speakers.



The **SGK6** Square Grille Kit complete the lineup and permits cosmetic finishing touches to match fixtures, HVAC accessories, and suit personal design tastes.



