

# NEW Kin IC6 Ultra Slim replaces Kin IC 6 Slim



KIN IC 6 Ultra Slim is 2.05" total depth-previous KINIC6-SLIM model was 4". Our design incorporates a **fully enclosed dual function vented back box**, protecting all componentry against any physical damage or foreign intrusion yet allowing discreet venting for bass supplementation. Weather resistant drivers, can be used in covered outdoor applications and high humidity areas such as washrooms

Micro perf stainless-steel grills with **NEW weather resistant COATING ON GRILL**. Updated hardware for greater strength and durability. Suitable for any application, inside or out.

## Glass Fiber Woofer

Reinforced glass fiber flat-cone woofer can be used in covered outdoor applications and high humidity areas such as washrooms.

## Soft Dome Tweeter

1 inch PEI Optimized crossover componentry and dual phase deflectors on tweeter for increased dispersion.

**2.05" in Depth versus KIN IC 6 SLIM 4"**






## Specifications

<b>Model:</b>	<b>IC6 ULTRA SLIM</b>
<b>Design:</b>	6" Ultra Slim In-Ceiling Speaker
<b>Frequency Response:</b>	55 Hz - 25 kHz
<b>Recommended Power:</b>	25-100 W
<b>Woofers:</b>	6" Glass Fiber Flat Cone Double 'U' SURROUND woofer
<b>Tweeter:</b>	1" PEI Soft dome tweeter
<b>Impedance:</b>	8 ohm
<b>Sensitivity dB @1W-1M</b>	90dB
<b>Dimensions (r x d):</b>	236 x 52 mm / 9.29 x 2.05 in
<b>Weight:</b>	1.59 kg / 3.5 lb
<b>Cutout</b>	207 mm / 8.15 in
<b>Grill type:</b>	Weatherproof, magnetic, paintable, virtually bezel-less white metal
<b>Accessories/Options</b>	Pre-construction brackets
<b>Speaker Terminals:</b>	Spring loaded Gold Plated
<b>Speaker Wire:</b>	Accepts up to 12 gauge
<b>Dispersion pattern:</b>	75 degrees

## Pre-Construction Kit



The **PCK6** ULTRA SLIM kit is equipped with multiple points to connect the wings guarantees that contact with drywall is always within access.



Rotating clamps have brass inserts to prevent thread stripping. The stainless-steel machine bolts are thread-strip and rust resistant.