

# SPECIFICATION SHEET

## KIN Mini Flex



### Satin Finishes



Black



White

### Dimensions (Irregular cabinet design)

Width	13.5" / 34.3 cm
Height	5.6" / 14.2 cm
Depth	3.75" to 4.4" / 9.5 to 11.2 cm

As part of the KIN Mini series, the new KIN Mini Flex is conceived to be ultra-flexible, ultra-compact and ultra-capable. Up or down, recessed or flat-out, table top, on-wall or on-ceiling, it delivers perfect in-phase precision and accuracy. Even if arranged in an asymmetrical configuration the Flex maintains a balanced soundstage image. Beautifully crafted for simplicity of use, the Flex can be positioned as a left/right or center unit.

The KIN Mini Flex's extra-sensitive drivers offer beautifully detailed renditions, retaining their absolute linearity at extreme operating ranges and providing dependable distortion-free performance. The honeycomb cone structure is super light yet incredibly strong, eliminating unwanted vibrational resonance at high output levels while delivering pinpoint musical accuracy.

Perfect for multichannel use, they can be mounted on-wall horizontally or vertically or even upside down if positioned close to the ceiling. The slight front angle tilt allows for optimal downward diffraction. As mentioned, the Flex can even be ceiling mounted if required. That's true flexibility.

Magnetic grill included.

### Specifications

Break-in time	50 - 75 hours
Frequency Response	32 Hz - 40 kHz $\pm$ 3 dB
Impedance	6 ohms
Crossover Frequency	3.2 kHz electrical and mechanical
Recommended Power	20 - 120 W
Sensitivity	89 dB/W/m.
Woofer	Twin 4" / 10.16 cm high-performance die-cast aluminum framed woofers. MHex Cones.
Tweeter	Low resonance 0.75" / 1.9 cm soft dome with high excursion capabilities.